## Galaxy.





Elevate your space with the beauty of Galaxy tiles. Featuring a refined finish, these tiles are designed to elevate any room. Perfect for both walls and floors, their durability and versatility make them an ideal choice for residential or commercial spaces.

| PRODUCT TYPE:   | Glazed porcelain              |  |
|-----------------|-------------------------------|--|
| COLOURS:        | See colour options overleaf   |  |
| SIZES (1):      | 600x600                       |  |
| SURFACES:       | Microtech                     |  |
| EDGES:          | Rectified                     |  |
| USAGE:          | Suitable for floors and walls |  |
| TECHNICAL INFO: | See overleaf                  |  |
| VARIATION (2):  | V3                            |  |
| WARRANTY (3):   | 15 Years                      |  |
| ORIGIN:         | China                         |  |

(1) Sizes are nominal and may include a grout joint. (2) Variation is an inherent property of tiles and stone. (3) If further details are required regarding our warranty or terms please contact our team on sales@qcg.co.nz or 0800 525 585

## Galaxy.



## COLOURS:







Bone

Grey

Iron

SIZES:



| TECHNICAL CHARACTERISTICS  | STANDARD               | VALUE     |         |  |
|--|------------------------|-----------|---------|--|
| Compliant with standards EN 14411 annex G group Bla. Compliant with standards ISO 13006 annex G group Bla. |                        |           |         |  |
| • Water absorption   | EN ISO 10545-3         | <0.5%     |         |  |
| ❖ Frost Resistance   | EN ISO 10545-12        | ✓         |         |  |
| ▲ Chemical resistance  | EN ISO 10545-13        | ✓         |         |  |
| Size variation   | EN ISO 10545-2         | -         |         |  |
| I Thickness  | -                      | 8.8mm     |         |  |
| ♦ Hardness (MOHS)  | EN 101                 | -         |         |  |
| Faces  | -                      | -         |         |  |
| ♣ Breaking Strength  | EN ISO 10545-4         | -         |         |  |
|  |                        | Anti Slip | Natural |  |
|  | DIN 51130 (R) *        | -         | -       |  |
| Sup nesistance   | AS/NZS 4586:2013 (SRV) | -         | -       |  |
|  | Average BP (P)         | -         | -       |  |